

2501 Ludelle Street Fort Worth, Texas 76105 817-244-6212 Phone • 817-244-4024 Fax 888-350-6588 Sales • 800-423-9696 Tech E-mail:painless@painlessperformance.com Web: www.painlessperformance.com

40025

JAMB TAC FIVE CONTACT WIRELESS CONNECTOR INSTALLATION INSTRUCTIONS

- 1. RUN THE GROUND WIRE FROM THE DOME LIGHTS OR DEVICE YOU PLAN TO OPERATE TO THE DOOR POST THAT HAS THE JAMB TAC INSTALLED. (IF THE UNIT GROUNDS ITSELF USE THE POWER WIRE)
- 2. STRIP 1/4" OF INSULATION AND CRIMP THE RECTANGULAR CONNECTOR ON THE WIRE. SLIDETHE CONNECTOR OVER THE METAL TAB ON THE BACKOF THE CONTACT.
- 3. NOW STRIP 1/4" OF INSULATION FROM ANOTHER WIRE AND CRIMP THE ROUND BULLET CONNECTOR ON IT. PUT THE BULLET CONNECTOR ON THE THE STUD OF THE SWITCH.
- 4. RUN THE WIRE IN STEP 3 TO A GOOD GROUND. SEE NOTE BELOW.

NOTE: IF A POWER WIRE WAS USED INSTEAD OF GROUND, RUN THIS WIRE TO A FUSED POWER SOURCE.

THINGS TO REMEMBER

- 1. ALWAYS HAVE THE RIGHT SIZE FUSE FOR THE DEVICE.
- 2. THE CONTACT PLUS WITH THE METAL ON THE BACK IS ALWAYS INSTALLED IN THE DOOR POST **NOT** THE DOOR.
- 3. MAKE SURE THE ADJUSTMENT OF THE CONTACTS MENTIONED IN STEP 4 IS SET.
- 4. THE EXTRA BULLET CONNECTORS YOU FOUND IS FOR THE DOOR SIDE OF THE SWITCH SO THAT YOU CAN LOCK THIS PLUNGER (SO THAT IT WILL NOT VIBRATE OUT OF ADJUSTMENT).

40025.doc 1/03/96

and Return Policy

Chassis harnesses and fuel injection harnesses are covered under a lifetime warranty.

All other products manufactured and/or sold by Painless Performance are warranted to the original purchaser to be free from defects in material and workmanship under normal use. Painless Performance will repair or replace defective products without charge during the first 12 months from the purchase date. No products will be considered for warranty without a copy of the purchase receipt showing the sellers name, address and date of purchase. You must return the product to the dealer you purchased it from to initiate warranty procedures.

Copyright © 2007 by Perfect Performance Products, LLC